

# The effect of viewing angle on EUV spectra of laser produced Gadolinium plasmas

Colm O’Gorman<sup>1</sup>, Takamitsu Otsuka<sup>2</sup>, Bowen Li<sup>1</sup>, Thomas Cummins<sup>1</sup>, Deirdre Kilbane<sup>1</sup>, Padraig Dunne<sup>1</sup>, Emma Sokell<sup>1</sup>, Gerry O’Sullivan<sup>1</sup>, Weihua Jiang<sup>4</sup>, Akira Endo<sup>5</sup>, Noboru Yugami<sup>2,3</sup>, and Takeshi Higashiguchi<sup>2,3</sup>

<sup>1</sup>School of Physics, University College Dublin, Belfield, Dublin, Ireland

<sup>2</sup>Department of Advanced Interdisciplinary Sciences, and Center for Optical Research & Education (CORE) Utsunomiya University, Utsunomiya, Tochigi, Japan

<sup>3</sup>Japan Science and Technology Agency, Kanagawa, Saitama, Japan

<sup>4</sup>Department of Electrical Engineering, Kami-tomiokamachi 1603-1, Nagaoka, Niigata 940-2188 Japan

<sup>5</sup>Waseda University, Research Institute for Science and Engineering, Waseda University, Shinjuku, Tokyo, Japan




Fig. 5.2 Emission Spectra from Targets of Salts of the Elements from Cesium to Lutetium.

Figure 1: UTA emission from the elements of Cesium to Lutetium [1]




Figure 2: Schematic of two target geometries used and the different detection angles

## 4. Low Density Target




Figure 4: Emission spectra from 30% low density target compared to 100% for target geometry (b)

- A low density foam target was irradiated with the 10ns laser
- Emission spectra from this low density target did not show the same absorption effects due to a lower density plasma

## 6.Future Work




Figure 6: Schematic of an internal optical system to be used in future to give higher angular resolution [8]

- Higher angular resolution will be achieved by using an optical setup described by Morris[8], shown in figure 6
- Imaging of plasma expansion using 100ps gate camera
- Nomarski interferometry to quantify 2 dimensional density profile of expanding plasma plume

## 1.Introduction

- Gd LPPs coupled with La/B<sub>4</sub>C MLM to be used as a source for BEUVL at 6.xnm
- Spectral emission from laser produced plasmas varies as a function of viewing angle[2]
- This effect must be quantified for the measurement of conversion efficiency to be comparable in different experiments[3]

## 2.Experimental Setup

- A 150 ps and 10 ns 1064 nm, Nd:YAG laser pulse with energy of 160mJ and 300mJ irradiated the target.
- A range of power densities was achieved by varying the incoming laser energy.
- Emission spectra was recorded for 4 different experimental setups using a flat field grazing incidence spectrometer with a 1200/mm variable line spaced grating
- The time-integrated spectra were detected by a thermoelectrically cooled back-illuminated x-ray charge coupled device (CCD) camera

## 3. Emission Spectra




Figure 3: Emission spectra from the 10ns (blue) and 150ps (red) LPPs for the four different target geometries, shown in figure 2

- Emission spectra is shown to vary greatly as a function of viewing angle when the 7ns laser is used due to absorption by low ion stages in the periphery of the plasma[4,5].

- Emission from 150ps LPP is more isotropic due to a higher rate of plume expansion. The plasmas is also optically thinner

## 5. Comparison to CR model




Figure 5: Theoretical spectra of best fit to experimental spectra produced by the 150ps Laser, the inset shows the ion distribution at this temperature of best fit

- Cowan code[6] calculations weighted with a collisional radiative model[7] gives theoretical spectra at a given electron temperature
- Spectra from the 150 ps LPP was found to have the same plasma temperature for all target geometries
- Spectra from 10 ns LPP were unable to be fitted with a theoretical spectra
- 2D expansion and absorption effects must be taken into account

## 7.References

- [1] A Spectroscopic Study of Laser Produced Plasmas of the Rare Earth and Related Elements– G.O’ Sullivan– Ph.D Thesis – 1980
- [2] P. Hayden, J. White, A. Cummings, P. Dunne, M. Lysaght, N. Murphy, P. Sheridan, G. O’Sullivan Microelectron. Eng. **83** 699- 702 (2006)
- [3] K. L. Sequoia, Y. Tao, S. Yuspeh, R. Burdt and M.S. Tillack, Appl. Phys. Lett. **92**, 221505
- [4] J. Filevich, J. J. Rocca, E. Jankowska, E.C. Hammarsten, K. Kanizay, M. C. Marconi, S.J. Moon and V. N. Shlyaptsev Phys. Rev. E. **67**, 056409 (2003)
- [5] M. Richter, M. Meyer, M. Pahler, T. Prescher, E.v. Raven, B. Sonntag and H.-E. Wetzels, Phys. Rev. A **40** 7007 – 7019
- [6] R. D. Cowan ‘The Theory of Atomic Structure and Spectra’ University of California Press, Berkeley 1981.
- [7] D. Colombant and G.F Tonon – J. Appl. Phys., **44** (8) (1973)
- [8] O. Morris, P. Hayden, F. O’Reilly, N. Murphy, P. Dunne, and V. Bakshi, Appl. Phys. Lett. **91**, 081506 (2007)



**Acknowledgements:** A part of this work was performed under the auspices of MEXT (Ministry of Education, Culture, Science and Technology, Japan) and “Utsunomiya University Distinguished Research Projects.” One of the authors (T.H.) also acknowledges support from The Canon Foundation. The UCD group acknowledges support from Science Foundation Ireland under Principal Investigator Research Grant No. 07/IN.1/1771. We also are grateful to the Komatsu Corporation for providing the picosecond laser system.

contact: colmogorman@ucd.ie

